

尺寸 Dimensions (mm)

系列 Series	A	B	C	D	E	F	G	H	I	J	K	L
TG	16±1	6±0.8	0.8±0.05	12±1	9+0.8/-0.5	39.5±2	3.8±0.5	3.4±0.2	7.95±0.3	1.65±0.1	6.35±0.2	7.3±0.2

关键特性 Key Features

- 陶瓷外壳
Ceramic Tube
- 一次性过温保护
One-time Over Temperature Protection
- 合金型温度保险丝
Alloy Type Thermal-link
- 高工作电压
High Working Voltage
- 环保型产品
RoHS & REACH Compliant

应用领域 Applications

- 电池 Batteries
- 汽车电子 Automobile Electronic

特殊定制 Customized

接线电极形状可以定制。
The shape of connecting pole can be customized as required.




包装信息 Packaging Information

产品包装数量 QTY:
3kPCS/箱 Carton
外箱尺寸 Carton Size: (mm)
440 × 300 × 260

安规认证 Agency Approvals

- UL/cUL: E214712

技术参数 Specifications

型号 Model	额定 动作 温度 T_f (°C)	熔断 温度 Fusing Temp. (°C)	保持 温度 T_h (°C)	极限 温度 T_m (°C)	额定 电流 I_r (A)	额定 电压 U_r (V)			 REACH
							UL	cUL	
TG86	86	81±2	51	250	15	450DC			●
					20	400DC			●
					20	690AC			●
TG102	102	99±2	64	250	15	450DC			●
					20	400DC			●
					20	690AC			●
TG115	115	111±2	80	250	15	450DC			●
					20	400DC			●
					20	690AC			●
TG125	125	122±2	90	250	15	450DC	●	●	●
					20	400DC	●	●	●
					20	690AC	●	●	●
TG130	130	126±2	95	250	15	450DC			●
					20	400DC			●
					20	690AC			●
TG136	136	132±2	102	250	15	450DC			●
					20	400DC			●
					20	690AC			●
TG150	150	146±2	117	250	15	450DC			●
					20	400DC			●
					20	690AC			●